External Hard Drives are cheap, and they crash. Tape backup is reliable, but expensive and slow.

The PopDrive is reliable and portable. It offers the manageability you require at a price your clients can afford.

RAID1 Reliability

Keep your clients' data secure, even in the event of a crash. *PopDrive* contains *two* laptop hard drives that are always mirrored. If one fails, simply replace it with a new drive, which will automatically sync with the other working drive. You can remove or replace either hard drive as easily as changing a CD. No special knowledge or tools required.

eSata: Lightning-Fast Backups

Backing up data is vital, but it shouldn't take all day. PopDrive is 6 times faster than USB and 5 to 10 times faster than tape. Backups take 50-70% less time! This encourages clients to maintain a routine of regular backups and frees them to focus on running their businesses.

All Your Client's Data in a Portable, Compact Device

PopDrive fits in a pocket, pouch or purse, so it's convenient to carry and easy to move to safety in an emergency. It's all in a 7x4x1" device that weighs about a pound. Its capacity is defined by the data capacity of your computer's OS and what's available in 2.5" drives. PopDrive has ample space for everything you want to safeguard.

Stay in Control

PopDrive's management software makes it easy for you to manage all of your client's drives. Keep track with an event log, and set it to e-mail event notifications.

Affordable, Powerful Security

Small businesses need much more than the typical external drive, but tape drives are often financially out of reach. *PopDrive* provides better security than tape, yet it costs *30 to 50% less*.

TechSpecs

PopDrive™ Technical Specifications

DIMENSIONS: $6^{3}/8$ "L x 4"W x $1^{1}/8$ "H

WEIGHT: 13 oz. empty, 21 oz. with 2 hard drives

HARD DRIVES: Two 2.5" laptop hard drives, one on top of the other

CASE: Aluminum

POWER: 5v, 2a

EXTERNAL eSata - 3Gb/s, USB2.0 - 480Mb/s CONNECTORS:



WIDTH: 2.5"

MAX HEIGHT: 10.5mm
INTERFACE: Sata

DATA CAPACITY: Limited only by the operating system of the connected computer

Software Requirements: Windows Systems

- » Intel Pentium-III 500MHz equivalent or faster
- Windows XP, Windows 2003 Server, Windows 2008 Server, Windows Vista, or Windows 7 with the latest Service Packs
- » CD-ROM drive
- 64 MB of RAM (minimum)
- 250 MB of free disk space
- Super VGA (800 x 600) or higher resolution display with at least 256 colors
- Mouse or compatible pointing device
- » SATA connection: SATA host controller with Port Multiplier support
- » USB connection: USB 1.0 or 2.0 direct host connection or USB hub

Software Requirements: Macintosh Systems

- » PowerMac G5, MacBook Pro or Mac Pro
- » MacOS X, 10.1 (or later)
- » CD-ROM drive
- » Mouse or compatible pointing device
- » SATA connection: SATA host controller with Port Multiplier support
- USB connection: USB 1.0 or 2.0 direct host connection or USB hub

